



**World's
Strongest
Bond™**

MirrorWeld™

**Rear View
Mirror
Adhesive**

Strength 3000 PSI

Set time 2 minutes

Cures in 1 hour

Easy to Use

Resists:

- Impact
- Moisture
- Humidity
- Heat
- Vibration

ADHESIVE: 0.014 FL. OZ. (0.4mL)

ACCELERATOR: 0.02 FL. OZ. (0.6mL)

WARNING: IRRITANT, FLAMMABLE. Read cautions on back panel.




MirrorWeld™

Rear View Mirror Adhesive

30322

About MirrorWeld™

MirrorWeld is a specially formulated adhesive specifically designed to bond rear view mirrors to windshields. It can be used to install new mirrors, as well as re-attach existing mirrors that have fallen off. This strong and fast-acting adhesive can also be used to bond other metal & glass items, ceramics & jewelry.



- 1 Prepare:** Use red tape/pencil/crayon to mark old location of mirror button (mark on outside windshield). Thoroughly clean & remove old adhesive from inside of windshield and metal button (if metal button is previously used).
- 2 Remove:** Note which side of mirror button faces up, then remove it from mirror bracket.
- 3 Activate:** Open Activator Wipe by pulling on both sides of packet at the top of package. Fold packet back to use.
- 4 Apply:** Use Activator to wipe both the marked area on the inside of the windshield and the side of the button that will bond to the windshield.
- 5 Dry:** Allow Activator to dry for 30 seconds.
- 6 Adhesive:** Apply a single drop of adhesive to metal button.
- 7 Attach:** Make sure button is right-side up. Press button onto marked location on windshield and hold for 2 minutes.
- 8 Wait:** Allow a minimum of minimum of 1 hour before mounting mirror to button. Adhesive gains full strength in 24 hours.

Do not try to remove mirror once installed. For best results, apply in temperatures between 50°-75°F (10° to 24°C). Use on metal buttons only, NOT plastic buttons.

WARNING:

EYE AND SKIN IRRITANT, FLAMMABLE LIQUID, MAY CAUSE AN ALLERGIC SKIN REACTION.

Contains Isopropyl Alcohol, Acrylic and Methacrylic Resins, N-Phenylacetohydrazide. DO NOT ingest or allow contact with skin or eyes. Keep away from fire and flame. Professionally launder contaminated clothing. Wear protective clothing, gloves, and eyewear while using.

FIRST AID:

IF SWALLOWED or on **SKIN** or **EYES** rinse with water & seek immediate medical attention. Remove any contaminated clothing. If skin irritation or rash occurs seek medical attention.

KEEP OUT OF THE REACH OF CHILDREN.

Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed. Ground and bond container and receiving equipment.

J-B Weld Company | P.O. Box 483 | Sulphur Springs, TX USA 75483
or visit: www.jbweld.com

Made in China
Product No. **33701**